

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A bootstrap circuit comprising a thin film transistor wherein:
a channel forming region of the thin film transistor ~~comprising~~ comprises a polycrystalline semiconductor, and
the thin film transistor is a depletion mode transistor.
2. (Original) The bootstrap circuit according to claim 1,
wherein the thin film transistor is directly connected to an output terminal.
3. (Original) The bootstrap circuit according to claim 1,
wherein the polycrystalline semiconductor film is provided over either a quartz substrate or a glass substrate.
4. (Original) A bootstrap circuit comprising a thin film transistor wherein:
a channel forming region of the thin film transistor comprises a polycrystalline semiconductor which is formed by crystallizing an amorphous silicon, and
the thin film transistor is a depletion mode transistor.
5. (Original) The bootstrap circuit according to claim 4,
wherein the thin film transistor is directly connected to an output terminal.
6. (Original) The bootstrap circuit according to claim 4,

wherein the polycrystalline semiconductor film is provided over either a quartz substrate or a glass substrate.

7. (Currently Amended) A driver circuit comprising:

a shift register;

a buffer circuit electrically connected to the ~~[[sift]]~~ shift register, comprising a source follower circuit comprising a thin film transistor; and

an analog memory electrically connected to the buffer circuit,

wherein:

a channel forming region of the thin film transistor comprises a polycrystalline semiconductor, and

the thin film transistor is a depletion mode transistor.

8. (Original) The driver circuit according to claim 7,

wherein the thin film transistor is directly connected to an output terminal.

9. (Original) The driver circuit according to claim 7,

wherein the polycrystalline semiconductor film is provided over either a quartz substrate or a glass substrate.

10. (Currently Amended) A driver circuit comprising:

a shift register;

a buffer circuit electrically connected to the ~~[[sift]]~~ shift register, comprising a source follower circuit comprising a thin film transistor; and

an analog memory electrically connected to the buffer circuit,

wherein:

a channel forming region of the thin film transistor comprises a polycrystalline semiconductor which is formed by crystallizing an amorphous silicon, and

the thin film transistor is a depletion mode transistor.

11. (Original) The driver circuit according to claim 10,
wherein the thin film transistor is directly connected to an output terminal.

12. (Original) The driver circuit according to claim 10,
wherein the polycrystalline semiconductor film is provided over either a quartz
substrate or a glass substrate.

13. (Currently Amended) A driver circuit comprising:
a shift register;
a buffer circuit electrically connected to the ~~[[sift]]~~ shift register, comprising a
bootstrap circuit comprising a thin film transistor; and
an analog memory electrically connected to the buffer circuit,
wherein:
a channel forming region of the thin film transistor comprises a polycrystalline
semiconductor, and
the thin film transistor is a depletion mode transistor.

14. (Original) The driver circuit according to claim 13,
wherein the thin film transistor is directly connected to an output terminal.

15. (Original) The driver circuit according to claim 13,
wherein the polycrystalline semiconductor film is provided over either a quartz
substrate or a glass substrate.

16. (Currently Amended) A driver circuit comprising:
a shift register;

a buffer circuit electrically connected to the ~~[[sift]]~~ shift register, comprising a bootstrap circuit comprising a thin film transistor; and
an analog memory electrically connected to the buffer circuit,
wherein:

a channel forming region of the thin film transistor comprises a polycrystalline semiconductor which is formed by crystallizing an amorphous silicon, and
the thin film transistor is a depletion mode transistor.

17. (Original) The driver circuit according to claim 16,
wherein the thin film transistor is directly connected to an output terminal.

18. (Original) The driver circuit according to claim 16,
wherein the polycrystalline semiconductor film is provided over either a quartz substrate or a glass substrate.

19. (Currently Amended) A display device comprising:
an insulating surface;
a signal line over the insulating surface;
a scanning line over the insulating surface;
a pixel electrically ~~connecting~~ connected to the signal line and the scanning line; and

a driver circuit electrically ~~connecting~~ connected to the scanning line,
comprising:

a shift register;
a buffer circuit electrically connected to the ~~[[sift]]~~ shift register, comprising a bootstrap circuit comprising a thin film transistor; and
an analog memory electrically connected to the buffer circuit,
wherein:

a channel forming region of the thin film transistor comprises a polycrystalline semiconductor, and

the thin film transistor is a depletion mode transistor.

20. (Original) The display device according to claim 19,
wherein the thin film transistor is directly connected to an output terminal.

21. (Original) The display device according to claim 19,
wherein the polycrystalline semiconductor film is provided over either a quartz substrate or a glass substrate.

22. (Currently Amended) A display device comprising:
an insulating surface;
a signal line over the insulating surface;
a scanning line over the insulating surface;
a pixel electrically ~~connecting~~ connected to the signal line and the scanning line; and

a driver circuit electrically ~~connecting~~ connected to the scanning line,
comprising:

a shift register;

a buffer circuit electrically connected to the ~~[[sift]]~~ shift register, comprising a bootstrap circuit comprising a thin film transistor; and

an analog memory electrically connected to the buffer circuit,

wherein:

a channel forming region of the thin film transistor comprises a polycrystalline semiconductor which is formed by crystallizing an amorphous silicon, and

the thin film transistor is a depletion mode transistor.

23. (Original) The display device according to claim 22,
wherein the thin film transistor is directly connected to an output terminal.

24. (Original) The display device according to claim 22,
wherein the polycrystalline semiconductor film is provided over either a quartz
substrate or a glass substrate.